



HIGHWAY RIB M140Z

NORTH AMERICA, SOUTH AND CENTRAL AMERICA,
EUROPE, THE MIDDLE EAST, AFRICA, OCEANIA



4
TBR

The M140Z, TOYO TIRES' highway rib truck & bus radial, has been developed to emphasize its improved wear performance and retreadability in a wide variety of operating conditions ranging from short, middle to long highway hauls. Its casing construction, profile, functional straight rib tread appearance and compound designed under DSOC II, TOYO TIRES' advanced tire design technology, result in M140Z's excellent performance over the competitors.

Rim Dia.	TIRE SIZE	LOAD INDEX/ SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
							OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
22.5	275/70 R22.5	148/145M	-	TL	BL	13.6	962	275	447	294	8.25	7.50 - 8.25
20	1100 R20	150/146K	-	TT	BL	13.9	1082	292	503	322	8.00	7.50 - 8.50
	1000 R20	146/143K	-	TT	BL	14.5	1051	277	489	306	7.50	7.00 - 8.00
	1000 R20	144/142K	-	TT	BL	14.5	1051	277	489	306	7.50	7.00 - 8.00
	900 R20	140/137K	-	TT	BL	13.0	1011	255	470	282	7.00	6.50 - 7.50
	825 R20	133/131K	-	TT	BL	12.5	971	234	452	258	6.50	6.00 - 7.00

[TYPE] TT: TUBE TYPE, TL: TUBELESS

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.