EUROPE, THE MIDDLE EAST, AFRICA, OCEANIA



HIGHWAY RIB



The M149, a super single trailer tire, has been developed to deliver superior wear performance with improved durability under tough operating conditions on trailers or front axle usage ranging from local to national haul operations. With the state-of-the-art TBR design technology, i.e., FEM analysis and systematic field evaluations, the M149 has been carefully designed and successfully accomplished its design goal as a new generation super single.

Rim Dia.	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	PLY RATING	TYPE	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION			
							overall DIA. (mm)	overall Width (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)	MEASURING RIM (Inch)	ALTERNATE RIM (Inch)
22.5	385/55 R22.5	160K	-	TL	BL	15.0	1009	378	469	402	11.75	11.75 - 12.25
	385/65 R22.5	160K	-	TL	BL	15.9	1079	376	502	397	11.75	11.75 - 12.25

[TYPE] TL: TUBELESS

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.