



PROXES 4

The Proxes 4, an all-season UHP radial, meets the increasing demand for affordable all-season performance with a stylish and attractive tread and sidewall design. Covering 25 to 55 series with V and W speed-rates, the Proxes 4 offers a wide selection in plus-sizing applications for a variety of contemporary sedans and coupes. In order to achieve excellent dry and wet handling performance, "T-mode", TOYO TIRES' advanced tire design technology, has been successfully applied for its development.

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
30	25	265/25ZR30	99W XL	BL	7.3	895	260	433	283	9.5	9.50
28	25	275/25ZR28	99W XL	BL	7.9	846	273	408	298	10.0	10.00
26	25	275/25ZR26	98W XL	BL	7.9	798	273	384	298	10.0	10.00
24	25	275/25ZR24	96W XL	BL	8.4	749	270	359	294	10.0	10.00
		275/30ZR24	101W XL	BL	8.4	777	272	370	296	9.5	9.00 - 10.00
	30	255/30ZR24	97W XL	BL	8.2	763	255	365	278	9.0	8.50 - 9.50
22	30	305/25ZR22	99W XL	BL	8.4	712	306	339	334	11.0	10.50 - 11.50
		265/30ZR22	97W XL	BL	8.3	719	265	342	289	9.5	9.00 - 10.00
		255/30ZR22	95W XL	BL	8.2	715	250	340	273	9.0	8.50 - 9.50
		245/30ZR22	92W XL	BL	8.1	710	240	338	262	8.5	8.00 - 9.00
	35	235/30ZR22	90W XL	BL	8.1	706	241	337	263	8.5	8.50
20	30	255/35ZR22	99W XL	BL	8.2	738	253	349	276	9.0	8.50 - 10.00
		295/25ZR20	95W XL	BL	8.4	660	295	313	322	10.5	10.00 - 11.00
		295/30ZR20	101W XL	BL	8.4	684	297	323	324	10.5	10.00 - 11.00
		255/30ZR20	92W XL	BL	8.2	662	254	314	277	9.0	8.50 - 9.50
	35	235/30ZR20	88W XL	BL	8.0	653	238	311	259	8.5	8.50
		215/30ZR20	82W XL	BL	7.9	638	215	305	234	7.5	7.50
		275/35ZR20	102W XL	BL	8.4	698	273	328	298	9.5	9.00 - 11.00
		255/35ZR20	97W XL	BL	8.2	687	258	324	281	9.0	8.50 - 10.00
		245/35ZR20	95W XL	BL	8.1	680	244	321	266	8.5	8.00 - 9.50
	40	225/35ZR20	90W XL	BL	7.9	671	228	318	249	8.0	7.50 - 9.00
		225/35 R20	90W XL	BL	7.9	671	228	318	249	8.0	7.50 - 9.00
		275/40ZR20	106W XL	BL	8.4	728	277	340	302	9.5	9.00 - 11.00
		245/40ZR20	99W XL	BL	8.1	702	245	330	267	8.5	8.00 - 9.50
45	255/45ZR20	105W XL	BL	8.2	738	256	344	279	8.5	8.00 - 9.50	
	245/45ZR20	103W XL	BL	8.1	729	244	340	266	8.0	7.50 - 9.00	
19	30	295/30ZR19	100W XL	BL	8.4	659	296	310	323	10.5	10.00 - 11.00
		265/30ZR19	93W XL	BL	8.3	642	268	303	292	9.5	9.00 - 10.00
	35	255/35ZR19	96W XL	BL	8.2	661	255	311	278	9.0	8.50 - 10.00
		245/35ZR19	93W XL	BL	8.1	654	248	308	270	8.5	8.00 - 9.50
		235/35 R19	91Y XL	BL	8.0	647	238	305	259	7.0	6.00 - 7.50
		235/35ZR19	91W XL	BL	8.0	650	248	307	270	8.5	8.00 - 9.50
		225/35ZR19	88W XL	BL	7.9	640	226	303	246	8.0	7.50 - 9.00
		215/35ZR19	85W XL	BL	7.8	632	218	300	238	7.5	7.00 - 8.50
18	35	215/35 R19	85W XL	BL	7.8	632	218	300	238	7.5	7.00 - 8.50
		275/35ZR18	99W XL	BL	8.4	646	273	302	298	9.5	9.00 - 11.00
		215/35ZR18	84W XL	BL	7.8	610	218	288	238	7.5	7.00 - 8.50
		215/35 R18	84W XL	BL	7.8	610	218	288	238	7.5	7.00 - 8.50

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
18	40	255/40ZR18	99W XL	BL	8.2	662	261	308	284	9.0	8.50 - 10.00
		245/40ZR18	97W XL	BL	8.1	653	248	305	270	8.5	8.00 - 9.50
		235/40ZR18	95W XL	BL	8.0	644	243	301	265	8.5	8.00 - 9.50
		225/40ZR18	92W XL	BL	7.9	638	230	299	251	8.0	7.50 - 9.00
		225/40 R18	92W XL	BL	7.9	638	230	299	251	8.0	7.50 - 9.00
		215/40ZR18	89W XL	BL	7.8	629	221	296	241	7.5	7.00 - 8.50
		215/40 R18	89W XL	BL	7.8	629	221	296	241	7.5	7.00 - 8.50
		205/40ZR18	86W XL	BL	7.7	623	218	293	238	7.5	7.00 - 8.00
	205/40 R18	86W XL	BL	7.7	623	218	293	238	7.5	7.00 - 8.00	
	45	255/45ZR18	103W XL	BL	8.2	688	256	319	279	8.5	8.00 - 9.50
		245/45ZR18	100W XL	BL	8.1	680	246	315	268	8.0	7.50 - 9.00
		235/45ZR18	98W XL	BL	8.0	671	236	312	257	8.0	7.50 - 9.00
		225/45ZR18	95W XL	BL	7.9	658	222	307	242	7.5	7.00 - 8.50
		225/45 R18	95W XL	BL	7.9	658	222	307	242	7.5	7.00 - 8.50
		215/45ZR18	93W XL	BL	7.8	645	210	302	229	7.0	7.00 - 8.00
	50	235/50ZR18	101W XL	BL	8.1	692	240	320	262	7.5	6.50 - 8.50
		225/50ZR18	95W	BL	7.9	683	228	317	249	7.0	6.00 - 8.00
	17	40	275/40ZR17	98W	BL	8.4	650	278	301	303	9.5
255/40ZR17			98W XL	BL	8.2	636	261	296	284	9.0	8.50 - 10.00
245/40ZR17			95W XL	BL	8.1	628	244	292	266	8.5	8.00 - 9.50
215/40ZR17			87W XL	BL	7.8	607	225	284	245	7.5	7.00 - 8.50
215/40 R17			87W XL	BL	7.8	607	225	284	245	7.5	7.00 - 8.50
205/40ZR17			84W XL	BL	7.7	598	218	281	238	7.5	7.00 - 8.00
205/40 R17			84W XL	BL	7.7	598	218	281	238	7.5	7.00 - 8.00
195/40 R17		81W XL	BL	7.6	587	203	276	221	7.0	6.50 - 7.50	
45		245/45ZR17	99W XL	BL	8.1	653	249	302	271	8.0	7.50 - 9.00
		235/45ZR17	97W XL	BL	8.0	644	239	299	261	8.0	7.50 - 9.00
		225/45ZR17	94W XL	BL	7.9	637	226	296	246	7.5	7.00 - 8.50
		225/45 R17	94W XL	BL	7.9	637	226	296	246	7.5	7.00 - 8.50
		215/45ZR17	91W XL	BL	7.8	629	214	293	233	7.0	7.00 - 8.00
		215/45 R17	91W XL	BL	7.8	629	214	293	233	7.0	7.00 - 8.00
		205/45ZR17	88W XL	BL	7.7	619	211	289	230	7.0	6.50 - 7.50
		205/45 R17	88W XL	BL	7.7	619	211	289	230	7.0	6.50 - 7.50
195/45 R17		85W XL	BL	7.6	608	194	285	211	6.5	6.00 - 7.50	
50		235/50ZR17	100W XL	BL	8.1	667	242	308	264	7.5	6.50 - 8.50
		225/50ZR17	98W XL	BL	8.0	658	229	304	250	7.0	6.00 - 8.00
		215/50ZR17	95W XL	BL	7.9	648	221	300	241	7.0	6.00 - 7.50
55		235/55ZR17	103W XL	BL	8.1	691	243	317	265	7.5	6.50 - 8.50
16	40	215/40 R16	86W XL	BL	7.8	576	222	269	242	7.5	7.00 - 8.50
		205/40ZR16	83W XL	BL	7.7	571	218	267	238	7.5	7.00 - 8.00
		205/40 R16	83W XL	BL	7.7	571	218	267	238	7.5	7.00 - 8.00
		195/40 R16	80V XL	BL	7.6	563	204	264	222	7.0	6.50 - 7.50
	45	205/45ZR16	87W XL	BL	7.7	593	211	276	230	7.0	6.50 - 7.50
		195/45 R16	84V XL	BL	7.6	583	194	272	211	6.5	6.00 - 7.50

PROXES 4

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
16	50	245/50 R16	97V	BL	8.1	650	248	298	270	7.5	7.00 - 8.50
		225/50 R16	96V XL	BL	7.9	632	230	291	251	7.0	6.00 - 8.00
		205/50 R16	91V XL	BL	7.7	612	212	283	231	6.5	5.50 - 7.50
		195/50 R16	88V XL	BL	7.6	605	198	281	216	6.0	5.50 - 7.00
	55	225/55 R16	99V XL	BL	7.9	653	234	299	255	7.0	6.00 - 8.00
		215/55 R16	97V XL	BL	7.8	645	223	296	243	7.0	6.00 - 7.50
		205/55 R16	94V XL	BL	7.7	634	214	292	233	6.5	5.50 - 7.50
		205/55 R16	91V	BL	6.4	634	214	292	233	6.5	5.50 - 7.50
15	45	195/45 R15	78V	BL	7.6	557	194	259	211	6.5	6.00 - 7.50
	50	225/50 R15	95V XL	BL	7.9	607	230	279	251	7.0	6.00 - 8.00
		205/50 R15	89V XL	BL	7.7	586	212	270	231	6.5	5.50 - 7.50
		205/50 R15	86V	BL	6.4	586	212	270	231	6.5	5.50 - 7.50
		195/50 R15	86V XL	BL	7.6	579	196	268	214	6.0	5.50 - 7.00
		195/50 R15	86V XL	BL	7.6	579	196	268	214	6.0	5.50 - 7.00
	55	205/55 R15	88V	BL	7.7	608	212	279	231	6.5	5.50 - 7.50
		205/55 R15	88V	BL	6.4	608	211	279	230	6.5	5.50 - 7.50
		195/55 R15	85V	BL	6.3	592	197	273	215	6.0	5.50 - 7.00
		185/55 R15	82V	BL	6.2	584	191	270	208	6.0	5.00 - 6.50

□: PROXES 4E

[LOAD INDEX] XL: EXTRA LOAD

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.