



# PROXES CF1

The Proxes CF1 has been developed for saloon vehicles to provide excellent handling performance with a highly advanced asymmetrical tread pattern. To achieve such advanced performance with improved overall comfort, the Proxes CF1 was launched.

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
18	55	225/55 R18	98V	BL	8.4	707	228	326	248	7.0	6.00 - 8.00
	60	225/60 R18	100W	BL	8.1	729	226	335	246	6.5	6.00 - 8.00
17	40	245/40 R17	91W	BL	8.2	627	247	292	269	8.5	8.00 - 9.50
		235/45 R17	94W	BL	8.2	643	239	298	261	8.0	7.50 - 9.00
	45	225/45 R17	94W XL	BL	8.2	634	222	295	242	7.5	7.00 - 8.50
		215/45 R17	87W	BL	8.2	625	212	291	231	7.0	7.00 - 8.00
	50	225/50 R17	94W	BL	8.4	660	229	305	250	7.0	6.00 - 8.00
		205/50 R17	93W XL	BL	8.2	645	210	299	229	6.5	5.50 - 7.50
	55	235/55 R17	103W XL	BL	8.5	690	238	317	259	7.5	6.50 - 8.50
		235/55 R17	99H	BL	8.5	689	241	316	263	7.5	6.50 - 8.50
		225/55 R17	101W XL	BL	8.4	681	228	313	249	7.0	6.00 - 8.00
		215/55 R17	98W XL	BL	8.4	670	220	309	240	7.0	6.00 - 7.50
	60	205/55 R17	91V	BL	8.2	658	203	304	221	6.5	5.50 - 7.50
		235/60 R17	102H	BL	8.2	715	238	326	260	7.0	6.50 - 8.50
65	215/60 R17	96H	BL	8.0	690	217	317	237	6.5	6.00 - 7.50	
	225/65 R17	102H	BL	8.2	726	226	331	246	6.5	6.00 - 8.00	
16	50	225/50 R16	92W	BL	8.4	631	233	291	254	7.0	6.00 - 8.00
		205/50 R16	87V	BL	8.2	611	210	283	229	6.5	5.50 - 7.50
		195/50 R16	88V XL	BL	8.1	602	201	279	219	6.0	5.50 - 7.00
	55	225/55 R16	99V XL	BL	8.4	651	227	299	248	7.0	6.00 - 8.00
		225/55 R16	96V	BL	8.4	650	230	298	251	7.0	6.00 - 8.00
		215/55 R16	97V XL	BL	8.3	644	223	296	243	7.0	6.00 - 7.50
		215/55 R16	93V	BL	8.3	642	223	295	243	7.0	6.00 - 7.50
		205/55 R16	94V XL	BL	8.2	630	207	290	226	6.5	5.50 - 7.50
		205/55 R16	91V	BL	8.2	630	207	290	226	6.5	5.50 - 7.50
		205/55 R16	94H XL	BL	8.2	630	207	290	226	6.5	5.50 - 7.50
	60	205/55 R16	91H	BL	8.2	630	207	290	225	6.5	5.50 - 7.50
		235/60 R16	100W	BL	8.2	688	239	313	261	7.0	6.50 - 8.50
		235/60 R16	104H XL	BL	8.2	688	239	313	261	7.0	6.50 - 8.50
		225/60 R16	98W	BL	8.1	676	226	308	246	6.5	6.00 - 8.00
		215/60 R16	99H XL	BL	8.0	665	218	304	238	6.5	6.00 - 7.50
		205/60 R16	96V XL	BL	7.9	652	206	299	225	6.0	5.50 - 7.50
205/60 R16		92H	BL	7.9	652	206	299	225	6.0	5.50 - 7.50	
65	195/60 R16C	99/97H	BL	7.8	642	195	250	213	6.0	5.50 - 6.50	
	215/65 R16	98W	BL	8.1	686	220	312	240	6.5	6.00 - 7.50	
15	50	215/65 R16C	106/104H	BL	8.1	687	223	268	243	6.5	6.00 - 7.00
		205/50 R15	86H	BL	8.2	586	210	270	229	6.5	5.50 - 7.50
		195/50 R15	82H	BL	8.1	578	197	267	215	6.0	5.50 - 7.00

# PROXES CF1

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
15	60	225/60ZR15	96W	BL	8.1	650	225	295	245	6.5	6.00 - 8.00
		215/60 R15	98V XL	BL	8.0	640	218	292	238	6.5	6.00 - 7.50
		205/60 R15	91V	BL	7.9	626	208	286	227	6.0	5.50 - 7.50
		205/60 R15	95H XL	BL	7.9	626	203	286	221	6.0	5.50 - 7.50
		205/60 R15	91H	BL	7.9	626	208	286	227	6.0	5.50 - 7.50
		195/60 R15	88V	BL	7.8	616	195	282	213	6.0	5.50 - 7.00
		195/60 R15	88H	BL	7.8	616	195	282	213	6.0	5.50 - 7.00
		185/60 R15	88H XL	BL	7.7	604	186	277	203	5.5	5.00 - 6.50
	175/60 R15	81V	BL	7.6	591	173	272	189	5.0	5.00 - 6.00	
	65	205/65 R15	95V	BL	8.0	647	204	294	222	6.0	5.50 - 7.50
		205/65 R15	99H XL	BL	8.0	647	204	294	222	6.0	5.50 - 7.50
		205/65 R15	95H	BL	8.0	647	204	294	222	6.0	5.50 - 7.50
		195/65 R15	91V	BL	7.9	635	196	290	214	6.0	5.50 - 7.00
		195/65 R15	95H XL	BL	7.9	635	196	290	214	6.0	5.50 - 7.00
		195/65 R15	91H	BL	7.9	635	196	290	214	6.0	5.50 - 7.00
		185/65 R15	88V	BL	7.8	620	184	284	201	5.5	5.00 - 6.50
		185/65 R15	88H	BL	7.8	620	184	284	201	5.5	5.00 - 6.50
	175/65 R15	84H	BL	7.7	609	175	279	191	5.0	5.00 - 6.00	
14	50	185/50 R14	77H	BL	8.0	546	185	252	202	6.0	5.00 - 6.50
	55	185/55 R14	80H	BL	8.0	560	188	257	205	6.0	5.00 - 6.50
	60	195/60 R14	86V	BL	7.8	591	195	270	213	6.0	5.50 - 7.00
		195/60 R14	86H	BL	7.8	591	195	270	213	6.0	5.50 - 7.00
		185/60 R14	82V	BL	7.7	578	186	265	203	5.5	5.00 - 6.50
		185/60 R14	82H	BL	7.7	578	186	265	203	5.5	5.00 - 6.50
		175/60 R14	79H	BL	7.6	566	173	260	189	5.0	5.00 - 6.00
		165/60 R14	75H	BL	7.7	554	166	255	181	5.0	4.50 - 6.00
	65	195/65 R14	89V	BL	7.9	609	196	277	214	6.0	5.50 - 7.00
		195/65 R14	89H	BL	7.9	609	196	277	214	6.0	5.50 - 7.00
		185/65 R14	86V	BL	7.8	595	187	271	204	5.5	5.00 - 6.50
		185/65 R14	86H	BL	7.8	595	187	271	204	5.5	5.00 - 6.50
175/65 R14		82H	BL	7.7	584	176	267	192	5.0	5.00 - 6.00	
13	60	185/60 R13	80H	BL	7.7	552	186	252	203	5.5	5.00 - 6.50
		175/60 R13	77H	BL	7.6	541	173	247	189	5.0	5.00 - 6.00

- : PROXES CF1S
- : PROXES CF1C

[LOAD INDEX] XL: EXTRA LOAD

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.