



PROXES TPT

The unidirectional tread pattern of the Proxes TPT offers comfortable ride and decreases pattern noise dramatically in comparison with the ordinary touring tires. Five variable pitches of tread block are applied, which helps realizing lower pattern noise by optimum arranging for the various pitch blocks. In addition, TOYO TIRES' unique computer simulation system for analyzing pattern noise was utilized on design stage for modifying tread pattern. Proxes TPT's low-noise performance is realized by combining the effects of these design methods.

RIM DIA.	ASPECT RATIO	TIRE SIZE	LOAD INDEX / SPEED SYMBOL	SIDE WALL	TREAD DEPTH (mm)	INFLATED DIMENSION		LOADED DIMENSION		MEASURING RIM WIDTH (Inch)	ALTERNATE RIM (Inch)
						OVERALL DIA. (mm)	OVERALL WIDTH (mm)	STATIC RADIUS (mm)	STATIC WIDTH (mm)		
17	45	225/45 R17	94V XL	BL	8.1	633	226	294	246	7.5	7.00 - 8.50
	50	235/50 R17	96V	BL	8.2	668	245	308	267	7.5	6.50 - 8.50
		225/50 R17	94V	BL	8.1	655	232	303	253	8.0	6.00 - 8.00
		215/50 R17	95V XL	BL	8.0	649	228	301	249	7.0	6.00 - 7.50
	55	235/55 R17	99V	BL	8.2	687	240	315	262	7.5	6.50 - 8.00
		235/55 R17	99H	BL	8.2	690	245	317	267	7.5	6.50 - 8.50
		225/55 R17	97V	BL	8.1	680	236	313	257	7.0	6.00 - 8.00
		215/55 R17	94V	BL	8.0	665	224	307	244	7.0	6.00 - 7.50
		215/55 R17	94H	BL	8.0	665	224	307	244	7.0	6.00 - 7.50
	16	50	195/50 R16	84V	BL	7.8	599	201	278	219	6.0
55		225/55 R16	95V	BL	8.1	651	232	299	253	7.0	6.00 - 8.00
		225/55 R16	95H	BL	8.1	651	229	299	250	7.0	6.00 - 8.00
		205/55 R16	94V XL	BL	7.9	629	212	290	231	6.5	5.50 - 7.50
		205/55 R16	94H XL	BL	7.9	629	212	290	231	6.5	5.50 - 7.50
60		235/60 R16	100H	BL	8.5	689	236	313	257	7.0	6.50 - 8.50
		225/60 R16	98V	BL	8.4	673	224	307	244	6.5	6.00 - 8.00
		225/60 R16	98H	BL	8.4	673	224	307	244	6.5	6.00 - 8.00
		215/60 R16	95V	BL	8.3	662	217	303	237	6.5	6.00 - 7.50
P205/60 R16		91V	BL	8.2	649	207	298	226	6.0	5.50 - 7.50	
65	205/65 R16	95H	BL	8.0	669	206	306	225	6.0	5.50 - 7.50	
15	55	195/55 R15	85V	BL	7.8	593	203	273	221	6.0	5.50 - 7.00
	60	225/60 R15	96V	BL	8.4	648	224	295	244	6.5	6.00 - 8.00
		225/60 R15	96H	BL	8.4	648	224	295	244	6.5	6.00 - 8.00
		P215/60 R15	93H	BL	8.3	636	218	290	238	6.5	6.00 - 7.50
		205/60 R15	91V	BL	8.2	623	207	285	226	6.0	5.50 - 7.50
		205/60 R15	91H	BL	8.2	623	207	285	226	6.0	5.50 - 7.50
	195/60 R15	88H	BL	8.1	612	199	281	217	6.0	5.50 - 7.00	
	65	P215/65 R15	95H	BL	8.1	657	219	298	239	6.5	6.00 - 7.50
		205/65 R15	94V	BL	8.0	642	206	292	225	6.0	5.50 - 7.50
		205/65 R15	94H	BL	8.0	642	204	292	222	6.0	5.50 - 7.50
195/65 R15		91H	BL	7.9	631	198	288	216	6.0	5.50 - 7.00	
185/65 R15	88H	BL	7.8	617	186	283	203	5.5	5.00 - 6.50		
14	60	P195/60 R14	85H	BL	8.1	587	198	268	216	6.0	5.00 - 7.00
		P185/60 R14	82H	BL	8.0	575	186	263	203	5.5	5.00 - 6.50
	65	185/65 R14	86H	BL	7.8	593	184	270	201	5.5	5.00 - 6.50
	70	P195/70 R14	90H	BL	8.9	630	201	285	219	6.0	5.00 - 6.50

[LOAD INDEX] XL: EXTRA LOAD

[SIDE WALL] BL: BLACK LETTERS

Data as of October 2010. All products of Toyo Tires are subject to continuous development. Toyo Tires reserves the right to change construction, materials or specifications without notice or obligation.